

DS TRP



PROTECTED ROLLERS MULTI-JET METER

DS TRP represents the ultimate multijet meter expression. Thanks to its mechanical transmission, it offers high metrological performance and is insensitive to external magnetic fields. Its "protected rollers" solution, first developed by Maddalena, ensures perfect legibility over time. Robust, long lasting and suitable for the most challenging environments, it is compatible with all types of water. It can be equipped with the latest remote data transmission technologies.

DS TRP

FEATURES


- Protected rollers multi-jet meter for cold water
- Ideal for utilities and outdoor installations
- MID-certified: R max 200
- DN: 15 to 50
- Pre-equipped for optional reed switch or static pulse emitter
- Health certifications available for a number of countries
- Mechanical transmission unaffected by external magnetic fields
- Mineral glass lens
- Number rollers, approval class and serial number are located in the protected part



TYPICAL ERROR CURVE



HEAD LOSS DIAGRAM



HYDRAULIC PERFORMANCE

Size	mm	15	20	25	32	40	50
	in	½	¾	1	1 ¼	1 ½	2

Modulo B no. TCM 142/08-4604

Modulo D no. 0119-SJ-A010-08

$Q_3/Q_1 = R$
Referred to installation position $H \uparrow \leq 200$

MID standard performance *

Q_3	m³/h	2,5	4	6,3	10	16	25
Q_4	m³/h	3,13	5	7,88	12,50	20	31,25

R **160**

Q_1	l/h	15,63	25	39,38	62,50	100	156,25
Q_2	l/h	25,01	40	63,01	100	160	250

* Other values of R available upon request.

TECHNICAL DATA

Maximum permissible error
between Q_1 and Q_2 (excluded) $\pm 5\%$

Maximum permissible error
between Q_2 (included) and Q_4 $\pm 2\%$ with water temperature $\leq 30^\circ\text{C}$
 $\pm 3\%$ with water temperature $> 30^\circ\text{C}$

Temperature class T30,T50

Flow profile sensitivity classes U0 - D0

Starting flow rate	l/h	4-5	7-9	16-18	22-24	28-30
--------------------	-----	-----	-----	-------	-------	-------

Head loss ΔP_{63}


Nominal pressure bar 16

Maximum reading m³ 100.000 1.000.000

Minimum reading m³ 0,05

Indicative weight	kg	1,45	1,61	2,3	2,4	4,5	14
-------------------	----	------	------	-----	-----	-----	----

DIMENSIONS



Size	mm	15	20	25	32	40	50
	in	½	¾	1	1 ¼	1 ½	2
Thread	in	G ¾ B	G 1 B	G 1 ¼ B	G 1 ½ B	G 2 B	G 2 ½ B
L	mm	105(V) – 110 – 130 – 145 – 160 – 165 – 170 – 190	160 – 190	220 – 260		300	300 – 270 (FL)
H	mm	112,5		123		163	175
h	mm	36,5		43		64,5	77
B	mm	97				130	154

COMMUNICATION MODULES



ARROW^{EVO} 868
SPLIT





ARROW^{WAN} 169
SPLIT





ARROW^{WAN} 868
SPLIT





ARROW^{WAN} NB-IoT
SPLIT





QUADRAPLUS



REED SWITCH