



BDV08012CS  
 ÷  
 BDV08230CS

Code	Power	Voltages Frequency	ED	Ambient temperature	Approvals
BDV08230AS	14,5 VA	230 ~ 50 240 ~ 60	100%	- 40°C + 60°C	CE
BDV08230AY	16 VA	230 ~ 50 240 ~ 60	100%	- 40°C + 60°C	CE - UL - CSA - VDE
BDV08230CS	8 W	230 ==	100%	- 40°C + 60°C	CE

info@idroenergiaitalia.it

ngwthshwln dnydqnd  
 r DUU GWIEVU t g h  
 x H q H D I  
 w H L V G t I I L F  
 H H I T O . w R D : w r A . ÷ I D f D R r L I E C D . I N

Ø I I L E R f R P U L D I H V G I Q L V I D  
 f R P U L D D G q R I V I E t I I L F  
 R M I H H . q H F H : q h A . E . ÷ I D u D I L D . N S  
 y H O . C M T . H S M L H T H H O  
 H E R D O J . L I R : I C R H U L D I D F I W  
 I H R I R : I C M P R O F L I R

NOMINAL VOLTAGES DC + 10% - 5%  
 TOLERANCES: AC + 10% - 15%

The power values are indicative, as they change as a function of magnetic kit used and of the application sector of reference | Other voltages and power absorptions available on demand and for quantities.