

| VOLTAGES - Volt - | | 4,5 | 6 | 9 | 4,5 | 6 | 9 | 6 | 9 | 12 | 9 | 12 | 24 | 12 | 24 |
|--|---------------------|-----|---|----|-----|-----|---|-----|-----|----|-----|-----|----|-----|----|
| POWER - Watt - | | 2,5 | 5 | 10 | 1,5 | 2,5 | 5 | 1,5 | 2,5 | 5 | 1,5 | 2,5 | 10 | 1,5 | 5 |
| SERIES width | RESISTANCE Ω | | | | | | | | | | | | | | |
| BDA 30 mm CONNECTOR EN 175301-803 paragraph 5.3.1 | 7 | X | X | X | | | | | | | | | | | |
| | 14 | | | | X | X | X | | | | | | | | |
| | 26 | | | | | | | X | X | X | | | | | |
| | 58 | | | | | | | | | | X | X | X | | |
| | 115 | | | | | | | | | | | | | X | X |

CODES

DIMENSIONS:

B Width 30 - tube \varnothing 13

ELECTRICAL CONNECTIONS:

D connector EN 175301-803 paragraph 5.3.1

COIL HOUSING MATERIAL:

A PA - Black polyamide class F (155°C)

B D A 1 X 0 0 6 L S

POWER:

1 X 1.5 W
2 X 2.5 W
0 5 5 W
1 0 10 W

VOLTAGES:

0 0 4 V 4,5
0 0 6 V 6
0 0 9 V 9
0 1 2 V 12
0 2 4 V 24

APPROVALS:

S Without approval

FREQUENCY:

L Latching coils

NOMINAL VOLTAGE TOLERANCES:

DC + 10% -5%